Note: This README file refers to the contents of it's corresponding source tarball and the installation of amavis-new.

AUTO-STARTUP AND INSTALLATION INSTRUCTIONS

~~~
~~~

Before we can get it up and running we need to edit the `amavisd` config file. You can do this with `vi`, `emacs`, `pico`, BBEdit, TextEdit, etc.—pretty much whatever you want to. The file is `/etc/amavisd.conf` and you need to change the user and group that `amavis-new` runs as to "`clamav`" You'll also want to take a look at where the spam and virus notifications go and the name/location of any AV software files. This file defines the spam and virus policies on your mail server. Let me say that again to make sure you understand. This file determines all of your spam and virus policies. As such you really should spend some time looking it over so that you don't embarrass yourself later.

The following setting should be used, don't forget to set $mydomaini:

```
$daemon_user  = 'clamav';     # (no default;  customary: vscan or
amavis)
$daemon_group = 'clamav';     # (no default;  customary: vscan or
amavis)
$MYHOME   = '/var/amavis';   # a convenient default for other
settings
$pid_file  = "$MYHOME/amavisd.pid";
$lock_file = "$MYHOME/amavisd.lock";
$unix_socketname = "$MYHOME/amavisd.sock";  # when using sendmail
milter
```

If you didn't install the BerkleyDB stuff set the following to disbaled it's use:

```
$enable_db = 0;             # enable use of BerkeleyDB/libdb (SNMP
and nanny)
$enable_global_cache = 0;   # enable use of libdb-based cache if
$enable_db=1
```

amavisd - changed/added:

Now we need to tell the binary where the config file is located.

```
my($config_file) = '/etc/amavisd.conf';  # default location of
config file
```

Next we need to edit the Postfix files.

First you need to add the following line to `/etc/postfix/main.cf`; it will tell Postfix to run `amavisd` as a content filter before delivery.

```
content_filter=smtp-amavis:[127.0.0.1]:10024
```

Now add the following to `/etc/postfix/master.cf`:

```
#
# ======================================================
#                      amavis-new
# ======================================================
#
smtp-amavis unix -       -       y       -       2       smtp
   -o smtp_data_done_timeout=1200
   -o smtp_send_xforward_command_yes
   -o disable_dns_lookups=yes
127.0.0.1:10025 inet n       -       y       -       -       smtpd
   -o content_filter=
   -o local_recipient_maps=
   -o relay_recipient_maps=
   -o smtpd_restriction_classes=
   -o smtpd_client_restrictions=
   -o smtpd_helo_restrictions=
   -o smtpd_sender_restrictions=
   -o smtpd_recipient_restrictions=permit_mynetworks,reject
   -o mynetworks=127.0.0.0/8
   -o strict_rfc821_envelopes=yes
   -o smtpd_error_sleep_time=0
   -o smtpd_soft_error_limit=1001
   -o smtpd_hard_error_limit=1000
   -o receive_override_options=no_header_body_checks
```

STARTUP ITEM(if using with ClamAV see Alternate Startup Item)

~~~
~~~

AUTO-STARTUP AND INSTALLATION INSTRUCTIONS FOR USE WITH CLAMAV

~~~
~~~